



Chair with upholstered seat and backrest and solid beech wood frame. Small version.



Frame Solid beech legs and interior frame.

Seat Beech plywood covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3 (25 kg/m3 and 40 kg/m3).

Back Covered in flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3 (25 kg/m3 and 40 kg/m3).

Other materials Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Accessories Polypropylene, felt or steel glides.

Leather

Leather

Cat L1
First categorie cow leather (21)

Cat L3
Polished full grain leather (21)

Fabrics

Fabrics				Faux Leather			
Cat 1 Microfibr (14) Jacquard 3 (15) Jacquard 1 (10) Sprint (25) Xtreme (25) Urban (25)	Cat 2 Jacquard 2 (15) High Tech One (5) Main Line Flex (25)	Cat 4 Remix 2 (49)	Cat 6 Clara (24)	Cat 8 Divina 3 (56) Willow (13) Tonus 3 (64)	Cat 9 Divina MD (27) Divina Melange (24) Hallingdal 65 (58) Steelcut Trio 2 (49)	Cat 1 Ecopiel 1 (14)	Cat 2 Ecopiel 2 (14)
Cat 4 Cava 3 (49) Field (24)		Cat 5 Messenger 4 (43) Plot (33) Blazer (25)	Cat 7 Sudden (24)			Cat 5 Ledger (32)	

Wood finish

Beech

311	301	378	322	336	364	372	369	381

Premium finish and wood

601	641	661	380	645L NCS 2005-Y20R Sand	646L NCS S 4005-Y20R Basalt Grey	642L RAL 3013 Cayenne Red	605L NCS S 6502-B Dark Grey	606L RAL 1005 Yellow Mustard

Resistance
and
Quality

ISO9001
UNE-EN 16139:2013

Fireproof

B.S. 5852 Part 2 Crib V
California Technical Bulletin 117
California Technical Bulletin 133
CS/FAR 25.853
French Arrêté du 28 Août
UNE-EN 1021-1:2006
UNI 9175 M-1

Sustainability

ASTM D5116 (VOCS Emissions)
FSC
GECA 28-2006 v2- Furniture and Fittings (modified 2010) Level B
ISO14001
PEFC

Glides

