

Flauta H1000 Spiga

■ F2345030 - Black

Designed by Patricia Urquiola, Patricia Urquiola


Collection of wall-mounted light fittings with dual light emission, available in various lengths. The units are characterised by the surface etching in two refined variations: Flauta Riga, with vertical lines, and Flauta Spiga, characterized by an elegant and sophisticated angular pattern. Rounding out the device is a deflector accessory painted to match the finish of the lamp body. It can be installed as desired on the upper or lower head to create a decorative effect with reflected light. The structure is made of aluminium treated with a chemical conversion process for effective resistance to atmospheric agents. The powder coating of the body is available in various finishes according to the QUALICOAT standard. LED light source included. Integrated 220–240 V electrical power with DALI dimmer. Comes with deflector for optional installation on the upper or lower head. LED light source included. Integrated 220–240 V electrical power with DALI dimmer. Comes with deflector for optional installation on the upper or lower head.

Main specifications

Mounting	Wall	Autoprotected Lamp	No
Environment	Indoor dry	Source Power (W)	12
	location	System Power (W)	12
Light source type	LED	Source Flux (lm)	493lm
LED type	LED Module	System Flux (lm)	493
Lamp holder	LED Module		

Optical

Lighting Type	Indirect, Direct
Lighting distribution	Asymmetric
CCT (K)	2700
CRI>	95
Cold Beam Lighting	No
Extreme Cut off	No



Electrical

Insulation class	II	Batteries Inside	No
Frequency (Hz)	50/60		
Main Voltage (Vac)	220-240		
Driver	Integrated		
Dimmable type	Dimmable 1-10V		

Physical

Colour	Black
Net weight (kg)	2.7
Gross weight (kg)	5.95
IP	40
IP external	40

