

RELIEF swivel with castors  
5036-4SCP  
Design Favaretto&Partners



BASE AND SUPPORT  
BASE E SUPPORTO  
BASE AND SUPPORT

 **00L**  
Polished aluminium 4 star base  
Base 4 razze alluminio pulito.  
Base de aluminio pulido de 4 radios

 **30**       **31**

SHELL  
SCocca  
CARCASA

Polypropylene + Glass fiber  
Polipropilene + Fibra di vetro  
Polipropileno + Fibra de vidrio

 **S020**       **R8022**       **S007**       **S503**       **S514**       **S529**       **R6013**

SUPPORT  
SUPPORTO  
SOPORTE

Polished die casting aluminium  
Alluminio presso fuso pulito.  
Aluminio fundido a presión pulido

CASTORS  
RUOTE  
RUEDAS PIVOTANTES

Perforated castors diam. 60 stem 11.  
Ruote forate diametro 60 perno 11.  
Ruedas pivotantes perforadas diám. 60 perno 11.

FEATURES  
CARATTERISTICHE  
CARACTERÍSTICAS

Painted aluminium base and support with epoxy-polyester powder with average thickness of 50 µ.  
Base e supporto in alluminio verniciato a polvere epossipoliestere con spessore medio di 50 µ.  
Base y soporte de aluminio con recubrimiento en polvo epoxi-poliéster con 50 µ de espesor medio.

CERTIFICATIONS  
CERTIFICAZIONI  
CERTIFICADOS



PKG  
IMBALLO  
EMBALAJE

Pkg	A(cm)	B(cm)	h(cm)	MC	PCS	Weight (kg)
59	63	85,5	0.32	1	12,82	

RELIEF swivel with castors upholstered seat panel  
5036-4SCS  
Design Favaretto&Partners



BASE AND SUPPORT

BASE E SUPPORTO  
BASE AND SUPPORT

Polished aluminium 4 star base  
Base 4 razze alluminio pulito.  
Base de aluminio pulido de 4 radios



SHELL

SCOCCA  
CARCASA

Polypropylene + Glass fiber  
Polipropilene + Fibra di vetro  
Polipropileno + Fibra de vidrio



UPHOLSTERY

TAPPEZZERIA  
TAPIZADOS

- A Space,Panarea
- B Eco Leather
- C Convert D,Velvety,Step, Step Melange, Nuvole
- D Reflect
- E Field, Oceanic, Yoredale
- F Steelcut Quartet,Canvas2
- G Divina3, Divina Melange, Fiord
- H Full Leather

COM Fabric(m)	COM Leather(m2)
0.65	0.50

SUPPORT

SUPPORTO  
SOPORTE

Polished die casting aluminium  
Alluminio presso fuso pulito.  
Aluminio fundido a presión pulido

CASTORS

RUOTE  
RUEDAS PIVOTANTES

Perforated castors diam. 60 stem 11.  
Ruote forate diametro 60 perno 11.  
Ruedas pivotantes perforadas diám. 60 perno 11.

FEATURES

CARATTERISTICHE  
CARACTERÍSTICAS

Painted aluminium base and support with epoxy-polyester powder with average thickness of 50 µ.  
Base e supporto in alluminio verniciato a polvere epossipoliesteri con spessore medio di 50 µ.  
Base y soporte de aluminio con recubrimiento en polvo epoxi-poliéster con 50 µ de espesor medio.

PKG

IMBALLO  
EMBALAJE

Pkg	A(cm)	B(cm)	h(cm)	MC	PCS	Weight (kg)
59	63	85,5	0.32	1	12,82	

RELIEF swivel with castors fully upholstered  
5036-4SCT  
Design Favaretto&Partners



BASE AND SUPPORT

BASE E SUPPORTO  
BASE AND SUPPORT

Polished aluminium 4 star base  
Base 4 razze alluminio pulito.  
Base de aluminio pulido de 4 radios



UPHOLSTERY

TAPPEZZERIA  
TAPIZADOS

Full upholstered shell  
Full upholstered shell  
Full upholstered shell

- A Space,Panarea
- B Eco Leather
- C Convert D,Velvety,Step, Step Melange, Nuvole
- D Reflect
- E Field, Oceanic , Yoredale
- F Steelcut Quartet,Canvas2
- G Divina3, Divina Melange, Fiord
- H Full Leather

COM Fabric(m)	COM Leather(m2)
1.00	1.40

SUPPORT

SUPPORTO  
SOPORTE

Polished die casting aluminium  
Alluminio presso fuso pulito.  
Aluminio fundido a presión pulido

CASTORS

RUOTE  
RUEDAS PIVOTANTES

Perforated castors diam. 60 stem 11.  
Ruote forate diametro 60 perno 11.  
Ruedas pivotantes perforadas diám. 60 perno 11.

FEATURES

CARATTERISTICHE  
CARACTERÍSTICAS

Painted aluminium base and support with epoxy-polyester powder with average thickness of 50 µ.  
Base e supporto in alluminio verniciato a polvere epossipoliestere con spessore medio di 50 µ  
Base y soporte de aluminio con recubrimiento en polvo epoxi-poliéster con 50 µ de espesor medio.

PKG

IMBALLO  
EMBALAJE

Pkg	A(cm)	B(cm)	h(cm)	MC	PCS	Weight (kg)
59	63	85,5	0.32	1	12,82	