

AIR

TECHNICAL INFORMATION

H 1600



L 600
W 400

Cabinet (L/H or R/H, 3 shelves)

Carcass and shelves

- 18 mm MFC (melamine) with 0,5 mm ABS edges.

Back

- 18 mm MFC (melamine).

Doors

- Doors with hinges from 18 mm MFC (melamine) with 1 mm ABS edges.
- No handles.

Fittings

- Cams with connecting bolts;
- Fast assembling hinges (does not require any tools to connect hinges and plates);
- Without soft closing.

Plastic legs

- Black plastic height levelling feet, H=23 mm +10 mm.

H 855



L 1600
W 400

Cabinet placed on bench (2 desks)

Carcass and shelves

- 18 mm MFC (melamine) with 0,5 mm ABS edges.

Doors


- Doors from 18 mm MFC (melamine) with 1 mm ABS edges;
- No handles.

Metal supports

- Welded metal construction from metal tube 12 mm;
- Powder coated metal;

Fittings

- Cams with connecting bolts;
- Fast assembling hinges (does not require any tools to connect hinges and plates);
- Gas spring;
- With soft closing.



MATERIALS

Melamine:



P U M1 M1PP PPM1 M1UU UUM1 M1N1

Metal:



E M

QUALITY STANDARD

- LST CEN/TR 14073-1:2004
- LST CEN/TR 14073-2:2004

GUARANTEE

- 5 year

ORDERING EXAMPLE

Code structure

