




5838	frame/seat
NY/New York-crystal	
SH/Shanghai-black	
RO/Rome-crystal	
PA/Paris-black	
MI/Milan-black	

Material
Seat: fabric-covered polyurethane
Cover: 100% polyester
Frame: transparent or mass-dyed polycarbonate

	level reached
EN 1022:2005	Compliant
EN 16139:2013 + AC2013	Compliant
EN 1728:2012 + AC 2013	
6.4	(maximum level) L2
6.5	(maximum level) L2
6.6	(maximum level) L2
6.10	(maximum level) L2
6.11	(maximum level) L2
6.15	(maximum level) L2
6.16	(maximum level) L2
6.17	(maximum level) L2
6.18	(maximum level) L2
6.20	(maximum level) L2
6.24	(maximum level) L2
6.25	(maximum level) L2
6.26	(maximum level) L2

****IT UNI 9175, EN1021 fire reaction test**
class 1 IM ministerial certification
MI1848D20D1IM00020
UK Standard BS 7176
"Medium Hazard" - S.I. 1324
US CALIFORNIA Standard TB 117

	width	height	depth	seat width/height	arms height	unit weight kg.
5838	54	80	53	39/47	53	8.080



packaging	quantity	weight kg.	volume m ³	size
5838	1	6.830	0.145	58X43X58
	1	5.180	0.114	53X44X49