



Armchair with upholstered seat and backrest and solid beech wood frame. Low back version.



Frame	Solid beech legs and interior frame.
Seat	Beech plywood covered with flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3 (25 kg/m3 and 40 kg/m3).
Back	Covered in flexible flame retardant polyurethane foam with density between 55 lb/ft3 and 88 lb/ft3 (25 kg/m3 and 40 kg/m3).
Arms	Solid beech.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.
Accessories	Polypropylene, felt or steel glides.
Leather	<div>Leather</div> <div>Cat L1 First categorie cow leather (21)</div> <div>Cat L3 Polished full grain leather (21)</div>

Fabrics	<div>Fabrics</div> <div>Cat 1 Microfibra (14) Jacquard 3 (15) Jacquard 1 (10) Sprint (25) Xtreme (25) Urban (25)</div> <div>Cat 2 Jacquard 2 (15) High Tech One (5) Main Line Flex (25)</div> <div>Cat 4 Cava 3 (49) Field (24)</div> <div>Cat 4 Remix 2 (49)</div> <div>Cat 5 Messenger 4 (43) Plot (33) Blazer (25)</div> <div>Cat 6 Clara (24)</div> <div>Cat 7 Sudden (24)</div> <div>Cat 8 Divina 3 (56) Willow (13) Tonus 3 (64)</div> <div>Cat 9 Divina MD (27) Divina Melange (24) Hallingdal 65 (58) Steelcut Trio 2 (49)</div> <div>Faux Leather</div> <div>Cat 1 Ecopiel 1 (14)</div> <div>Cat 2 Ecopiel 2 (14)</div> <div>Cat 5 Ledger (32)</div>
---------	---

Wood finish  
Beech



Premium  
finish and  
wood



Resistance  
and  
Quality

ISO9001  
UNE-EN 16139:2013

Fireproof

B.S. 5852 Part 2 Crib V  
California Technical Bulletin 117  
California Technical Bulletin 133  
CS/FAR 25.853  
French Arrêté du 28 Août  
UNE-EN 1021-1:2006  
UNI 9175 M-1

Sustainability

ASTM D5116 (VOCS Emissions)  
FSC  
GECA 28-2006 v2- Furniture and Fittings (modified 2010) Level B  
ISO14001  
PEFC

Glides

