ideal lux

Zig zag

rev. 27-04-2022



General info

DECORATIVO - Wall

Heat-sink body totally made of aluminum sheet of 6 mm thickness. White or black powder paint finish or plated brass. Integrated LED source.

Ean	8021696179292
Item	ZIG ZAG AP D29 BIANCO 3000K
Installation	Wall
Guarantee	5 years
Gross weight	0.53 kg
Volume	0.002025 m³

Technical info

Net weight	0.45 kg
Insulation class	I
Protection index	IP20
Compliance	-
Operating temperature	0° ~ +40 °C K
Dimmer	No dimmerable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	Integrato, incluso
	SI (solo personale qualificato), elettronico

Source info

Integrated source	Modulo LED integrato
Repleaceable source	Sì
Power	LED 12,5W
Emission	Indiretta
Max consuption	max 12 W
Features LED	LED SMD SAMSUNG
CCT	3000 K
Duration LED (t. 25°c)	50000 h
CRI	> 80
Light beam flux	1450 lm
Useful light flux	1310 lm

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com