

FELUCA 4 legs
5011-4LGW
Design BrogliatoTraverso



FRAME

TELAIO
BASTIDOR

Metal frame in oval tube 40x20 mm, thickness 1,5 mm, accordingly with UNI EN 10305-3 rule
Metal frame in oval tube 40x20 mm, thickness 1,5 mm, accordingly with UNI EN 10305-3 rule
Metal frame in oval tube 40x20 mm, thickness 1,5 mm, accordingly with UNI EN 10305-3 rule



SEAT AND BACKREST

SEDUTA E SCHIENALE
ASIENTO Y RESPALDO

Plywood ash, 10,5 mm thickness
Plywood ash, 10,5 mm thickness
Plywood ash, 10,5 mm thickness



FINISHING

FINITURA
ACABADO

Painted frame with epoxy-polyester powder with average thickness of 50 µ
Telaio verniciato con polveri epossipoliesteri spessore medio di 50 µ
Bastidor con recubrimiento en polvo epoxipoliéster con 50 µ de espesor medio.

FEET

PIEDINI
PIES DE APOYO

Polypropylene
Polipropilene
Polipropileno

UPHOLSTERY

TAPPEZZERIA
TAPIZADOS

Request information from the sales department

CERTIFICATIONS

CERTIFICAZIONI
CERTIFICADOS



PKG

IMBALLO
EMBALAJE

Pkg	A(cm)	B(cm)	h(cm)	MC	PCS	Weight (kg)
	42	60	97	0.24	2	14