

Every day we are surrounded by all sorts of sounds, from whirring fans, chatting colleagues and ringing phones to the background noise of a radio. Unwanted noise can have a negative effect on people, disrupting concentration and increasing stress levels.


Decibel by Johanson specialises in creating a better environment for everyone to work and live in.

We develop sound absorbers and acoustic diffuser panels that really do make a difference. Our products are the result of many years' experience of design and close collaboration with acoustic engineers, backed up by systematic acoustic analyses and tests conducted in accordance with approved standards.

Of the five senses that humans have evolved – smell, hearing, taste, touch and sight – three are particularly important for survival. These are smell, hearing and sight. At Decibel we have chosen to focus our work on hearing and on issues that are key to understanding how sound is transmitted, perceived and absorbed.

Human hearing developed primarily to alert us to dangers and to localise the source of a noise so that we could determine the best escape route. Today the situation is very different. We live in an information society where it is absolutely essential to be able to hear what is being said in order to acquire and systematise information.

To mitigate distracting noise Decibel by Johanson has developed sound absorbers that make it easier to concentrate on the task in hand. We believe that emulating natural features of the outdoor environment and recreating them in indoor spaces is a relevant way to recognise the value of all our senses – eye, ear and soul.




### THE SCIENCE AND UNDERSTANDING OF SOUND

Sound is energy. Sound needs air in order to travel from point A to point B. It also needs a 'trigger' that causes an object to vibrate, such as a hammer striking a nail or a finger plucking a guitar string.

A third component in the transmission of sound is our ear and its ability to detect the sounds we hear. Different sounds are the result of contrasts in energy and variations in wavelengths. A bass sound has more energy and longer wavelengths. That's why, during a concert, we may experience pressure on our chest from the vibration of not

the bass: this is because the air is, literally, being pressed against our body. The fact that the high energy content of a bass note can travel a long way may sometimes be perceived as disturbing. High-pitched sounds, however, have less energy and shorter wavelengths, so their energy dissipates quickly. Imagine, for example, the scenario of overhearing a conversation in the office next door. It is difficult to determine what is being said, because higher-pitched sounds are less able to penetrate the wall than those with a low pitch. The effect can be even more disturbing if one of those talking has a deep (bass) voice: it's



The human ear can detect frequencies between 20 and 20,000 Hertz (Hz). The voice frequency, however, is approximately 125-8,000 Hz. Vowels such as A, E, O, I and U are pronounced loudest, so these vowels belong to a low frequency band. Voiced consonants such as M, R, V and B are in the medium frequency range, while the unvoiced consonants F, P, S and T are in the high frequency band, with F, T and S being particularly difficult to discern.


possible to distinguish any consonants, so all that we hear is a low 'rumbling'.


All of us have our own inbuilt hearing threshold, which is affected in different ways. Loud noises (in excess of 120 dB) can cause discomfort and pain – and our ears are less forgiving than our eyes. If our eyes are exposed to very bright light, we can squint or blink, and the consequence may be no more than a temporary halo in our field of vision. Loud noises, however, can seriously damage our hearing, causing tinnitus or leading to other permanent hearing impairments.

For most of us, poor light is preferable to an uncomfortable noise level.

Hearing also deteriorates with age. It is quite common for our hearing acuity to diminish with increasing rapidity as we grow older, making it hard for us to distinguish between words such as 'sound', 'found' and 'round'. Instead we either have to use context and the speaker's lip movements, or increase the volume in some way in order to interpret what is being said.

## THE FUNCTION OF SOUND ABSORBERS IN DIFFERENT ENVIRONMENTS







### **OFFICES**

In a room without sound absorbers there is always a certain amount of unwanted background noise and half-heard conversations that are perceived as disturbing.

Solution: We install sound absorbers on both side-walls in order to reduce the overall noise level. We also fit sound absorbers on one non-parallel surface to improve the acoustic environment even further by making it easier for workers to concentrate and to distinguish what is being said to them.





### **CLASSROOMS**

In a classroom there is usually just one main source of sound (the teacher's voice). This can pose a serious problem, because while pupils on the front row hear only direct sound, those further back in the room also have to cope with reflected sounds that bounce off the walls and ceiling. Solution: The illustrations above show how energy in the sound waves transmitted by the teacher is absorbed by the panels and captured within the absorbent material instead of being reflected. As all those in the room now hear only direct sound, this increases speech clarity and understanding.

### UNIQUE COLLABORATION

The Ecophon Inside™ symbol guarantees that a product bearing this mark has been developed in conjunction with Ecophon. The sound-absorbent materials are designed and manufactured to satisfy criteria for optimum technical performance and a visually appealing form. Both core and surface materials have been specially chosen to meet the most stringent quality standards.

Our carefully engineered designs and approved eco-friendly materials provide an effective answer to the challenges of today's noisy world. All our products have been painstakingly tested by accredited laboratories in accordance with the latest standards for the relevant market. Production processes for the various components are environmentally certified according to ISO 14001 and all manufacturing is carried out in house in Hyllinge and Markaryd in Sweden.

Ecophon Inside<sup>™</sup> is a registered trademark and must not be copied or used in any way without prior approval from Saint-Gobain Ecophon AB.







### BOW

DESIGN - BÖTTCHER & KAYSER

An arc-shaped thin MDF on the diagonal stretches up the fabric like a tent, creating an interesting three-dimensional shape.


Depending on how the absorbent is directed and dressed, you can create infinite combinations and geometric patterns.


Then add a directed light and exciting

shadow formations appear.

































### CHESTERFIELD

DESIGN - JOHAN LINDSTÉN

The name and inspiration for this design come from the iconic, traditional Chesterfield sofa – a timeless design that has become synonymous with deep-buttoned quilting. The height differences of the quilting give the sound absorber its characteristic look, while also enhancing its acoustic and absorbent properties.


























































# DECIBEL FACTS PRODUCT DETAILS INSTALLATION

### **BOW**



HEIGHT 60 CM WIDHT 60 CM DEPTH 11 CM WEIGHT 4 KG

### MATERIAL

Ecophon Inside Core in MDF-board Suspension with wooden beam is standard Fabric

### **OPTIONS**

Magnets for mounting, neodym 4 x ø20 x 6 mm 200 cm wooden beam when installing several panels in width (not in combination with magnets)

### **ACOUSTIC PROPERTIES**

### Frekvens i Hz

63 125 250 500 1000 2000 4000 Aw 0,07 0,22 0,76 1,09 1,13 1,12 1,14 1,0

Absorption Class A

Testad enl ISO 354:2003 ISO 11654:1997 ISO 20189:2018

### FIRE TEST

Tested according to EN ISO 11925-2


### UPHOLSTERY MATERIAL

The fabrics for our sound absorbers are carefully selected and tested according to the standard set by all the manufacturers.

PG0		PG1	
Camira	Cara	Gabriel	Soul
Camira	Carlow	Gabriel	Soul Solange
Camira	Era 170	Gabriel	Twist
Gabriel	Event Screen	Gabriel	Twist Melange
Gabriel	Hush	Gabriel	Xpress (2,0)
		Kvadrat	Remix Screen

### MOUNTING


Suspension with wooden beam 4 pcs (standard)



Wooden beam wall 1 pcs




Suspension with magnets 4 pcs (optional)







# **FACETT**



HEIGHT 60 CM WIDHT 60 CM DEPTH 11 CM WEIGHT 4 KG

# MATERIAL

Ecophon Inside Core in MDF-board Suspension with wooden beam is standard Fabric

# **OPTIONS**

Magnets for mounting, neodym 4 x ø20 x 6 mm 200 cm wooden beam when installing several panels in width (not in combination with magnets)

# **ACOUSTIC PROPERTIES**

# Frekvens i Hz

4000 63 125 250 500 1000 2000 Αw 0,06 0,26 0,77 1,18 1,24 1,10 1,06 1,0

Absorption Class A

Testad enl ISO 354:2003 ISO 11654:1997 ISO 20189:2018

# FIRE TEST

Tested according to EN ISO 11925-2


# **UPHOLSTERY MATERIAL**

The fabrics for our sound absorbers are carefully selected and tested according to the standard set by all the manufacturers.

PG0		PG1	
Camira	Cara	Gabriel	Soul
Camira	Carlow	Gabriel	Soul Solange
Camira	Era 170	Gabriel	Twist
Gabriel	Event Screen	Gabriel	Twist Melange
Gabriel	Hush	Gabriel	Xpress (2,0)
		Kvadrat	Remix Screen

# **MOUNTING**

Suspension with wooden beam 4 pcs (standard)



Wooden beam wall 1 pcs




Suspension with magnets 4 pcs (optional)









# CHESTERFIELD / LOOP/ ROMB FRAME FAMILY







HEIGHT 60,5 CM WIDTH 60,5 CM DEPHT 6 CM WEIGHT 7 KG

# MATERIAL

Ecophon Inside

Metal frame in selectable RAL color

Wire grids

Back piece in MDF-board

Suspension with wooden beam is standard Fabric

# **OPTIONS**

Magnets for mounting, Rubber-coated neodym 4 x Ø45 x 6 mm. 200 cm wooden beam when installing several panels in width (not in combination with magnets)

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

63	125	250	500	1000	2000	4000	Aw
0,03	0,19	0,62	1,11	1,19	1,13	1,1	1

Absorption Class A

Tested according to ISO 354 och ISO 11654

#### FIRE TES

Chesterfield / Loop / Romb is tested according to SS-EN ISO 11925-2


# UPHOLSTERY MATERIAL

The fabrics for our sound absorbers are carefully selected and tested according to the standard set by all the manufacturers.

PG0		PG1	
Camira	Cara	Gabriel	Soul
Camira	Carlow	Gabriel	Soul Solange
Camira	Era 170	Gabriel	Twist
Gabriel	Event Screen	Gabriel	Twist Melange
Gabriel	Hush	Gabriel	Xpress (2,0)
		Kvadrat	Remix Screen

# MOUNTING


Suspension with wooden beam 4 pcs (standard)



Wooden beam wall 1 pcs




Suspension with magnets 4 pcs (optional)







# **CLAMP CEILING**



HEIGHT	59,5 CM	HEIGHT	79,5 CM
WIDTH	59,5 CM	WIDTH	79,5 CM
DEPHT	4,5 CM	DEPHT	4,5 CM
TOTAL DEPTH	6,5 CM	TOTAL DEPTH	6,5 CM
TOTAL WEIGHT	3.6 KG	TOTAL WEIGHT	6.6 KG

# MATERIAL

Ecophon Inside Fabric

Metal clamp for ceiling in selectable RAL color Wire 80 cm / 150 cm Adjustable cable lock with hook Ceiling fastener in selectable RAL color

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

63	125	250	500	1000	2000	4000	Aw
0,02	0,17	0,62	1,16	1,16	1,09	1,01	0,95

Absorption Class A

Tested according to ISO 354 och ISO 11654

# FIRE TEST

Clamp is tested according to SS-EN ISO 11925-2

# **UPHOLSTERY MATERIAL**

The fabrics for our sound absorbers are carefully selected and tested according to the standard set by all the manufacturers.

PG0		PG1	
Camira	Cara	Gabriel	Soul
Camira	Carlow	Gabriel	Soul Solange
Camira	Era 170	Gabriel	Twist
Gabriel	Event Screen	Gabriel	Twist Melange
Gabriel	Hush	Gabriel	Xpress (2,0)
		Kvadrat	Remix Screen


# MOUNTING

Metal clamp 1 pcs



Wire 3 pcs 80 cm / 150 cm Adjustable cable lock with hook 3 pcs










# **CLAMP FLOOR**



HEIGHT	170 CN
WIDTH	120 CN
DEPHT	4,8 CN
TOTAL DEPTH	45 CN
WEIGHT	7,4 K
FRAME WEIGHT	Γ 4,6 K

# MATERIAL

Ecophon Inside

Fabric

Metal frame in selectable RAL color

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

63	125	250	500	1000	2000	4000	N10
0,07	0,63	1,43	2,61	2,87	2,46	2,19	4,5

Absorption Class A

Tested according to ISO 354 och SS 25269

# FIRE TEST

Clamp is tested according to SS-EN ISO 11925-2

# **UPHOLSTERY MATERIAL**


The fabrics for our sound absorbers are carefully selected and tested according to the standard set by all the manufacturers.


PG0		PG1	
Camira	Cara	Gabriel	Soul
Camira	Carlow	Gabriel	Soul Solange
Camira	Era 170	Gabriel	Twist
Gabriel	Event Screen	Gabriel	Twist Melange
Gabriel	Hush	Gabriel	Xpress (2,0)
		Kvadrat	Remix Screen





# **CLAMP WALL SQUARE / ROUND**





 HEIGHT
 59,5/79,5 CM

 WIDTH
 59,5/79,5 CM

 DEPHT
 4 CM

 TOTAL DEPTH
 6 CM

 TOTAL WEIGHT
 2,6/5,2 KG

DIAMETER Ø60/80 CM WIDTH 4 CM TOTAL DEPTH 6 CM TOTAL WEIGHT 2,8/3,6 KG

**MOUNTING** 

For wall mounting

# MATERIAL

Ecophon Inside

Fabric

Metal frame in selectable RAL color

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

63 125 250 500 1000 2000 4000 Aw 0,02 0,17 0,62 1,16 1,16 1,09 1,01 0,95

Absorption Class A

Tested according to ISO 354 och ISO 11654

# FIRE TEST

Clamp is tested according to SS-EN ISO 11925-2

# **UPHOLSTERY MATERIAL**

The fabrics for our sound absorbers are carefully selected and tested according to the standard set by all the manufacturers.

PG0		PG1	
Camira	Cara	Gabriel	Soul
Camira	Carlow	Gabriel	Soul Solange
Camira	Era 170	Gabriel	Twist
Gabriel	Event Screen	Gabriel	Twist Melange
Gabriel	Hush	Gabriel	Xpress (2,0)
		Kvadrat	Remix Screen





# **CUBIC 16/32**

HEIGHT	100 CM	200 CM	
WIDTH	40 CM	40 CM	
DEPHT	40 CM	40 CM	
WEIGHT	17 kg	23 kg	

# MATERIAL

Ecophon Inside

Wooden shell

Fabric Gabriel Xpress

For other fabrics request a quote

With wheels for easy placement

Top / bottom in metal, with optional RAL-colour, black or white finish

# FIRE TEST


Will be tested shortly

# **ACOUSTIC PROPERTIES**

The absorbent placed in the middle of the room

# Frequency in Hz


63	125	250	500	1000	2000	4000	N10
0,4	1,34	2,0	2,59	3,18	3,24	3,22	3,8



The absorbent placed in a corner (bass trap).

# Frequency in Hz


63	125	250	500	1000	2000	4000	N10
0,49	2,09	1,97	2,10	2,04	1,86	1,75	5,6







# **FREQUENCY**



HEIGHT	80 CM	80 CM	60 CM	60 CM	40 CM
WIDTH	80 CM	40 CM	60 CM	30 CM	40 CM
TOTAL DEPTH	4/8/12 CM	4/8/12 CM	4/8/12 CM	4/8/12 CM	4/8/12 CM
WEIGHT	5,5/6,5/8 KG	2,5/3/4 KG	3/4/5 KG	1,5/2/2,5 KG	1,5/1,7/2 KG

# MATERIAL

**Ecophon Inside** Back piece in MDF-board Suspension with wooden beam is standard Fabric

# **OPTIONS**

Magnets for mounting, neodym 4 x ø20 x 6 mm 200 cm wooden beam when installing several panels in width (not in combination with magnets)

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

63	125	250	500	1000	2000	4000	Aw
0,02	0,17	0,62	1,16	1,16	1,09	1,01	0,95

Absorption Class A

Tested according to ISO 354 och ISO 11654

# FIRE TEST

Frequency is tested according to EN ISO 11925-2


# **UPHOLSTERY MATERIAL**

The fabrics for our sound absorbers are carefully selected and tested according to the standard set by all the manufacturers.

PG0		PG1	
Camira	Cara	Gabriel	Soul
Camira	Carlow	Gabriel	Soul Solange
Camira	Era 170	Gabriel	Twist
Gabriel	Event Screen	Gabriel	Twist Melange
Gabriel	Hush	Gabriel	Xpress (2,0)
		Kvadrat	Remix Screen

# MOUNTING


Suspension with wooden beam 4 pcs (standard)



Wooden beam wall 1 pcs




Suspension with magnets 4 pcs (optional)







# **HERTZ & HERTZ PHOTO**



\*For special measurments request a quote.

# MATERIAL

30x60x5 40x40x5 40x80x5 60x60x5 80x80x5 120x30x5 120x60x5 120x120x5

Ecophon Inside Back piece in MDF-board Suspension with metal strip is standard Fabric

# **OPTIONS**

Magnets for mounting, neodym 4 x ø20 x 6 mm 200 cm wooden beam when installing several panels in width (not in combination with magnets)

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

63	125	250	500	1000	2000	4000	Aw
0,02	0,17	0,62	1,16	1,16	1,09	1,01	0,95

Absorption Class A

Tested according to ISO 354 och ISO 11654

# FIRE TEST

Hertz is tested according to SS-EN ISO 11925-2

# **UPHOLSTERY MATERIAL**

The fabrics for our sound absorbers are carefully selected and tested according to the standard set by all the manufacturers.

Hertz is now available with your own unique photo or motif. The print is certified based on the requirements for the fabric selection that allows the amount of air required to achieve the right performance on the products.

For price with your own photo/motif please contact Decibel customer support.

	PG1	
Cara	Gabriel	Soul
Carlow	Gabriel	Soul Solange
Era 170	Gabriel	Twist
Event Screen	Gabriel	Twist Melange
Hush	Gabriel	Xpress (2,0)
	Kvadrat	Remix Screen
	Carlow Era 170 Event Screen	Cara Gabriel Carlow Gabriel Era 170 Gabriel Event Screen Gabriel Hush Gabriel

# **MOUNTING**


Suspension with metal strip



Metal wall molding 1 pcs



Suspension with magnets 4 pcs (optional)







# **HERTZ FLOOR**

# MATERIAL

Core: Ecophon Inside

Frame: Birch plywood 40x18 mm

Metal fittings: Metal in selectable RAL color


Selectable fabric

# **FABRIC**

The fabrics we use for our sound absorbers are all carefully selected and tested according to the current standard used by manufacturers.

Prices on application for other fabrics an photo print.

PG0		PG1	
Camira	Cara	Gabriel	Soul
Camira	Carlow	Gabriel	Soul Solange
Camira	Era 170	Gabriel	Twist
Gabriel	Event Screen	Gabriel	Twist Melange
Gabriel	Hush	Gabriel	Xpress (2,0)
		Kvadrat	Remix Screen



<sup>\*</sup>The screens are flexible in size and can be produced in special measurements. Prices on request.

# **ACOUSTIC FACTS**

The screens and its sound absorbing abilities can be declared by using the standard of N10. This measuring method is developed by Acoustic Facts in cooperation with the Swedish Judicial Board for Public Lands and Funds, and describes the demands for a screen that is measured according the standard SS 25269.

# FIRE TEST


Testad enligt EN ISO 11925-2

# acoustic facts


Storlek (b×h i mm)	N <sub>10</sub> ≤ (Must be less than below)	Hertz floor
1200×1600	8	3,8
1200×1800	7	3,4
1000×1500	9	-
1000×1600	9	4,5
1000×1800	8	4,5

# **METAL FITTINGS**

Choose from the Decibel selection of colours – a total of 192 RAL colours, available both as solid colours (gloss 72) and in a subtly textured finish for an elegant matt surface. In addition we can offer 15 RAL colours in a mother-of-pearl finish.



# **HERTZ STRIPED**



# MATERIAL

Ecophon Inside Back piece in MDF-board Suspension with metal strip is standard Fabric

# **OPTIONS**

Magnets for mounting

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

125 250 1000 2000 4000 Aw 63 500 0,02 0,17 0,62 1,16 1,16 1,09 1,01 0,95

Absorption Class A

Tested according to ISO 354 och ISO 11654

# FIRE TEST

Hertz is tested according to SS-EN ISO 11925-2


# FABRIC

Gabriel Hush


For other fabrics request a quote.




# MOUNTING Suspension with metal strip



Metal wall molding 1 pcs



magnets 4 pcs (optional)



# **PHOTO FRAME**





Dimensions in (cm) 68x68x5 88x88x5 128x68x5

128x128x5

# MATERIAL

Ecophon Inside
Anodized aluminum frame
Certified print on fabric with high air permeability for good sound absorption
Suspension with metal strip is standard

# **IMAGE MOTIVES**

Choose an image from our image archive or attach your own material

# **OPTIONS**

RAL - painted frame For price request a quote

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

125 63 250 500 1000 2000 4000 Aw 0,17 0,02 0,62 1,16 1,16 1,09 1,01 0,95


Absorption Class A


Tested according to ISO 354 och ISO 11654





# **ILLUSION 60 / 120**





HEIGHT	60 CM	HEIGHT	120 CM
WIDTH	60 CM	WIDTH	30 CM
DEPTH	12 CM	DEPTH	12 CM
NEIGHT	2,7 KG	WEIGHT	2,7 KG

# MATERIAL

Ecophon Inside
Back piece in MDF-board
Suspension with wooden beam is standard
Fabric

# **OPTIONS**

Magnets for mounting, neodym 4 x ø20 x 6 mm 200 cm wooden beam when installing several panels in width (not in combination with magnets)

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

63	125	250	500	1000	2000	4000	Aw
0,03	0,19	0,61	1,02	1,02	1,12	1,16	1

Absorption Class A

Tested according to ISO 354 och ISO 11654

#### FIRE TEST

Illusion is tested according to SS-EN ISO 11925-2


# UPHOLSTERY MATERIAL

The fabrics for our sound absorbers are carefully selected and tested according to the standard set by all the manufacturers.

PG0		PG1	
Camira	Cara	Gabriel	Soul
Camira	Carlow	Gabriel	Soul Solange
Camira	Era 170	Gabriel	Twist
Gabriel	Event Screen	Gabriel	Twist Melange
Gabriel	Hush	Gabriel	Xpress (2,0)
		Kvadrat	Remix Screen

# MOUNTING


Suspension with wooden beam 4 pcs (standard)



Wooden beam wall 1 pcs



Suspension with magnets 4 pcs (optional)








<sup>\*</sup>For special measurments request a quote.

# **POST**



HEIGHT 59,5 CM
WIDTH 59,5 CM
DEPTH 6 CM
WEIGHT 3,8 KG

# MATERIAL

Ecophon Inside
Back piece in MDF-board
Suspension with wooden beam is standard
Fabric

# **OPTIONS**

Magnets for mounting, neodym 4 x ø20 x 6 mm 200 cm wooden beam when installing several panels in width (not in combination with magnets)

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

63	125	250	500	1000	2000	4000	Αw
0,02	0,17	0,62	1,16	1,16	1,09	1,01	0,9

Absorption Class A

Tested according to ISO 354 och ISO 11654

# FIRE TEST

Post is tested according to SS-EN ISO 11925-2


# **UPHOLSTERY MATERIAL**

The fabrics for our sound absorbers are carefully selected and tested according to the standard set by all the manufacturers.

PG0		PG1	
Camira	Cara	Gabriel	Soul
Camira	Carlow	Gabriel	Soul Solange
Camira	Era 170	Gabriel	Twist
Gabriel	Event Screen	Gabriel	Twist Melange
Gabriel	Hush	Gabriel	Xpress (2,0)
		Kvadrat	Remix Screen

# MOUNTING

Suspension with wooden beam 4 pcs (standard)



Wooden beam wall 1 pcs




Suspension with magnets 4 pcs (optional)







# **BEEHIVE**





HEIGHT 55 CM
WIDTH 47,5 CM
DEPTH 7,5 CM
WEIGHT 0,5 KG
AREA 0,26 M²
VOLUME 0,027 M³

# MATERIAL

Polyester Felt black / dark grey / light grey Gabriel Europost Magnets for mounting, 2 x ø30 x 6 mm

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

63	125	250	500	1000	2000	4000	Aw
0,0	0,1	0,5	1,0	0,9	0,9	1,0	0,6

Absorption Class C

Tested according to ISO 354:2003, ISO 25269:2013, ISO 11654:1997


# FIRE TEST

Tested according to EN ISO 11925-2





# MOUNTING

Magnets for mounting 2 pcs



# **BEEHIVE RECTANGULAR**





HEIGHT 55 CM
WIDTH 47,5 CM
DEPTH 7,5 CM
WEIGHT 0,8 KG
AREA 0,26 M²
VOLUME 0,032 M³

# MATERIAL Polyester Felt black / dark grey / light grey Gabriel Europost

Gabriel Europost
Magnets for mounting, 4 x ø30 x 6 mm

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

63	125	250	500	1000	2000	4000	Aw
0,0	0,1	0,5	1,0	0,9	0,9	1,0	0,6

Absorption Class C

Tested according to ISO 354:2003, ISO 25269:2013, ISO 11654:1997


# FIRE TEST

Tested according to EN ISO 11925-2




# MOUNTING

# Magnets for mounting 4 pcs



# **CROPFIELD**





HEIGHT 60,5 CM WIDTH 60,5 CM DEPTH 5,5 CM WEIGHT 0,9 KG AREA 0,36 M<sup>2</sup> VOLUME 0,038 M<sup>3</sup>

# MATERIAL

Polyester
Felt black / dark grey / light grey
Gabriel Europost
Magnets for mounting, 4 x ø30 x 6 mm

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

63	125	250	500	1000	2000	4000	Aw
0,0	0,1	0,5	1,0	0,9	0,9	1,0	0,6

Absorption Class C

Tested according to ISO 354:2003, ISO 25269:2013, ISO 11654:1997


# FIRE TEST

Tested according to EN ISO 11925-2





# MOUNTING

Magnets for mounting 4 pcs



# **VICTOR. THE EGGBOX**





MOUNTING

Suspension with

Mounting plate 180x40 2st

magnets 4 pcs



# MATERIAL

Polyester 70% (recyclable fibers) Hemp 30% (organic fibers) Suspension with magnets, 4 x ø20 x 5 mm

# **COLORS**







Purple dream





Grey stone

# **ACOUSTIC PROPERTIES**

Frequency in Hz

125 1000 2000 4000 Aw 63 250 500 0,0 0,05 0,55 0,5 0,20 0,85 0,75 0,9

Absorption Class D

Tested according to EN ISO 354:2003, EN ISO 11654:1997

# FIRE TEST

Tested according to EN ISO 11925-2



# **LEAVES**





HEIGHT	60,5 CM
WIDTH	60,5 CM
DEPTH	6,6 CM
WEIGHT	0,9 KG
AREA	0,36 M <sup>2</sup>
VOLUME	0,038 M <sup>3</sup>

# MATERIAL

Polyester Felt black / dark grey / light grey **Gabriel Europost** Magnets for mounting, 4 x ø30 x 6 mm

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

125 2000 4000 Aw 250 500 1000 0,1 0,5 0,6 0,0 1,0 0,9 0,9 1,0

Absorption Class C

Tested according to ISO 354:2003, ISO 25269:2013, ISO 11654:1997

# FIRE TEST

Tested according to EN ISO 11925-2




# MOUNTING

Magnets for mounting 4 pcs



# MOON



HEIGHT 90 CM
WIDTH 55 CM
DEPTH 9 CM
WEIGHT 0,9 KG
AREA 0,36 M²
VOLUME 0,064 M³

# MATERIAL

Polyester Felt black / dark grey / light grey Gabriel Europost Magnets for mounting, 3 x ø30 x 6 mm

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

63 125 250 500 1000 2000 4000 Aw 0,0 0,1 0,5 1,0 0,9 0,9 1,0 0,6

Absorption Class C

Tested according to ISO 354:2003, ISO 25269:2013, ISO 11654:1997


# FIRE TEST

Tested according to EN ISO 11925-2




# MOUNTING

Magnets for mounting 3 pcs



# **PEBBLE**





HEIGHT 60,5 CM WIDTH 60,5 CM DEPTH 7,5 CM WEIGHT 0,9 KG AREA 0,36 M<sup>2</sup> VOLUME 0,038 M<sup>3</sup>

# MATERIAL

Polyester Felt black / dark grey / light grey Gabriel Europost Magnets for mounting, 4 x ø30 x 6 mm

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

63 125 250 500 1000 2000 4000 Aw 0,0 0,1 0,5 1,0 0,9 0,9 1,0 0,6

Absorption Class C

Tested according to ISO 354:2003, ISO 25269:2013, ISO 11654:1997


# FIRE TEST

Tested according to EN ISO 11925-2




# MOUNTING

Magnets for mounting 4 pcs



# **RACE WALL**



HEIGHT 60,5 CM
WIDTH 60,5 CM
DEPTH 7,5 CM
WEIGHT 0,9 KG
AREA 0,36 M²
VOLUME 0,038 M³

# MATERIAL

Polyester
Felt black / dark grey / light grey
Gabriel Europost
Magnets for mounting, 4 x ø30 x 6 mm

# **ACOUSTIC PROPERTIES**

# Frequency in Hz

63 125 250 500 1000 2000 4000 Aw 0,0 0,1 0,5 1,0 0,9 0,9 1,0 0,6

Absorption Class C

Tested according to ISO 354:2003, ISO 25269:2013, ISO 11654:1997


# FIRE TEST

Tested according to EN ISO 11925-2



# MOUNTING

Magnets for mounting 4 pcs



# **RIB WALL**





HEIGHT 60 CM WIDTH 100 CM DEPTH 1,5 CM WEIGHT 2,5 KG AREA 0,6 M<sup>2</sup> VOLUME 0,06 M<sup>3</sup>

# MATERIAL

Polyester
Felt black / dark grey / light grey
Gabriel Europost
Magnets for mounting, 6 x ø30 x 6 mm

# ACOUSTIC PROPERTIES

# Frequency in Hz

63 125 250 500 1000 2000 4000 Aw 0,0 0,1 0,5 1,0 0,9 0,9 1,0 0,6

Absorption Class C

Tested according to ISO 354:2003, ISO 25269:2013, ISO 11654:1997


# FIRE TEST

Tested according to EN ISO 11925-2



# **MOUNTING**

Magnets for mounting 6 pcs





# CAD/BIM

Most of our products are downloadable as CAD/BIM objects for 3ds Max, Archicad, AutoCad 2D, DWG, AutoCad 3D, Material & Textures, Revit, SketchUp and pCon Planner.

# pCon

The perfect tool for managing everything from simple floor plans to the most complex 3D renderings, Thanks to pCon, producing customised solutions for your project has never been simpler. Powerful OFML data facilitates the entire configuration process from dimensions to the final price. Decibel by Johanson has many years' experience of preparing complete offers for our products.

If you are in need of any files in order to plan your design, please don't hesitate to contact us at Decibel.

# SUSTAINABILITY - A KEY PART OF OUR CONCEPT

Decibel by Johanson is tireless in its efforts to create new possibilities and improve the qualities of its products from a sustainability perspective. We place great emphasis on ethical, sustainable production and good working conditions, both in our own facilities and those of our suppliers.

# **CUS ON ALL COMPONENTS**

For all products bearing the Ecophon Inside label our partner and supplier is Ecophon, a company that takes sustainability very seriously and is able to account for the materials' environmental impact. More than 70 percent of the sound-absorbing glass wool core is made from recycled glass. (In a process that is unique in the world, glass bottles deposited in recycling stations in Sweden are recycled as sound absorbers.)

Ecophon was the first in the market to offer a product range made with a plant-based binder, saving the equivalent of 24,000 barrels of crude oil per year. Ecophon products also have a number of third-party certificates that ensure a healthy indoor environment. The production plant in Hyllinge in the south of Sweden

is powered by electricity from 100% renewable sources.

All our design panels are made of pressed polyester felt from recycled PET bottles.

# COVERINGS

The fabrics used in our sound absorbers are carefully selected and tested by the manufacturers in accordance with relevant standards.

Decibel aims to ensure that none of the properties of the various components are altered or compromised in any way.

# **MÖBELFAKTA**

The majority of our products meet strict Möbel-fakta criteria. This comprehensive and updated reference and labelling system is synonymous with professionalism and quality throughout the entire value chain, all the way to the end user. The system is based on three areas of requirements:

- Quality
- Environment
- Social responsibility

# DECIBEL BY JOHANSON – SOUND ABSORBERS THAT MAKE A CLEAR DIFFERENCE

Our products are developed not only with people's ears in mind – they are designed to have eye-appeal as well. We want our sound absorbers to be as attractive to look at as they are effective in creating a pleasant acoustic environment. The visual design and acoustic properties work together to produce the kind of truly harmonious setting that helps promote a sense of well-being and improves productivity.



www.decibelab.se