

## SPECIFICATION

Range: **OVERSIZE LUX**  
Design: **Marc Sadler**

“Snowsound Technology” sound-absorbing element suspended from the ceiling with cables, with lighting element.

Panel description:

Both faces with convex section 36 mm thick, consisting of an internal padding in variable density polyester fiber. The density decreases moving towards the heart of the panel, which is covered on both sides with Trevira CS® polyester fabric, solidly applied to the padding. The panel is double sided, with same characteristics on both sides. It is characterized by the rigid edge obtained by the manufacturing process itself, without any supporting and/or stiffening frame. The central part it is die-cut to allow the fitting of the lamps.

The panel has an **Italian Class1** fire reaction and **Euroclass B-s2, d0**.

The panel is **Greenguard Gold** certified, which validates its low VOC emission and its contribution to the quality of the indoor environment.

The panel is **100% recyclable** and has no detectable formaldehyde content according to UNI EN 717-2. It does not contain felts or other organic materials that are hardly recyclable.

The panel has been tested in reverberation chamber according to UNI EN ISO 354 and obtained “**Acoustic Absorption Class A**”, in accordance with UNI EN ISO 11654.

Panel dimensions:      119x59 cm      119x119 cm  
                                 159x59 cm      159x119 cm

Lighting element description:

The lamp element made of epoxy powder-coated steel is positioned in the upper part of the panel and screwed to the frame with special screws. The diffuser is located inside the die cut of the panel.

(For the lighting technical characteristics of the lamps, please consult the card ST.007S-2)

Fixing kit description:

The panel is equipped at the top with a stiffening frame made of galvanized tubular steel with a rectangular section (40x10 mm, thickness 1,2 mm), which is fixed directly to the panel with self-tapping screws. The frame is equipped with 4 slots. They hold 4 cylindrical threaded elements  $\varnothing$  10 mm that grant precise height adjustment of the cables by means of a pressure system with safety lock; 4 steel cables  $\varnothing$  1.5 mm and 4 circular chromed steel plates  $\varnothing$  40 mm equipped with two holes for anchoring screws to the ceiling.

The products described in this data sheet are **CE marked**.



Available colors:

6046



Light blue

4086



Brick red

8007



Dark grey

4030



Carrot orange

4027



Red

8004



Silver grey

2005



Dove-grey

3008



Sun yellow

6075



Teal

0001



White

1008




Beige

7004



Light green

8002



Cool white

