




reddot award 2017
winner



9390/9391/9386/B9386/U9386
Z9386/9385/B9385/U9385/Z9385



9390 - B9386 - 9386
9385 - B9385



9391 - U9386
U9385

		class of insulation	direct mounting	degree of protection	power voltage	max. wattage	unit weight kg.
9390				IP 20	220-240	22W LED 2400lm 2700 K	2.700
9391				IP 20	120	19W LED 2400lm 2700 K	2.700
		diameter Ø	height diffuser	length min÷max			
		33	27	38÷232			
9386 B9386				IP 20	220-240	22W LED 2400lm 2700 K	2.700
U9386 Z9386				IP 20	120	19W LED 2400lm 2700 K	2.700
		Ø diameter	height				
		33	28				
9385 B9385 WITH DIMMER				IP 20	220-240	22W LED 2400lm 2700 K	3.140
U9385 Z9385 ON/OFF				IP 20	120	19W LED 2400lm 2700 K	3.140
		Ø diameter	height				
		33	53				

Material

transparent or mass-dyed
thermoplastic technopolymer

Frame: Polished or painted die-cast
aluminium

packaging	quantity	weight kg.	volume m ³	dimension
9390 / 9391	1	4.100	0.050	39X33X39
9386/B9386/U9386/Z9386	1	4,080	0,054	39X39X33
9385/B9385/U9385/Z9385	1	4.720	0.085	39X55X44