

Captain Flint Outdoor W1 Dimmable DALI

■ F011W20D030 - Black

Designed by Michael Anastassiades

Luminaire for wall-mounting with diffuse light emission and fixed head.

Rose, frame and cone in 316L polished or painted stainless steel or polished brass finishes. Structural parts have been treated with a chemical conversion process for effective resistance against atmospheric conditions. Diffuser in photo-recorded and injection molded UV-resistant opalescent polycarbonate. LED light source included.

Integrated 220-240V DALI dimmable electrical power.

Connection is quickly ensured in the rose with the plug & play electrical connection and the IP68 connector included. Clamp bracket included.


110V version upon request

Main specifications

Mounting	Ceiling and wall surface	Autoprotected Lamp	No
Light source replaceable	Replaceable (LED only) light source by a professional	Number of heads	1
LED type	LED array	Source Power (W)	9.5
Lamp category	LED	Source Flux (lm)	1055
Dimmable	Yes	System Flux (lm)	613

Optical

Lighting Type	Direct
Lighting distribution	Symmetric
CCT (K)	2700
CRI>	80
Cold Beam Lighting	No
Beam angle C0-180 (°)	112
Beam angle C90-270 (°)	112



Beam Angle: 112°		
h(m)	E(lx)	D(m)
1	217	2.95
2	54	5.91
3	24	8.86
4	14	11.81
5	9	14.76

Luminous flux luminaire
613 lm

Electrical

Insulation class	I	Dimmable type	Dimmable DALI
Frequency (Hz)	50-60	Batteries Inside	No
Main Voltage (Vac)	220-240	Power supply replaceable	Replaceable control gear by a professional
Driver	Integrated	Precabled	no
Dimmable	Yes	Emergency Type	No

Physical

Colour	Black	Length (mm)	336
Trim	No	Net weight (kg)	2.1
Orientations	Fixed	IP	65
Recessed depth (mm)	0		
Spot diameter (mm)	208		

Note

110V version upon request.

