

## Captain Flint Outdoor W1

■ F011W20A018 - Deep Brown

Designed by Michael Anastassiades

Luminaire for wall-mounting with diffuse light emission and fixed head.

Rose, frame and cone in 316L polished or painted stainless steel or polished brass finishes. Structural parts have been treated with a chemical conversion process for effective resistance against atmospheric conditions. Diffuser in photo-recorded and injection molded UV-resistant opalescent polycarbonate. LED light source included.

Integrated 220-240V ON/OFF electrical power.

Connection is quickly ensured in the rose with the plug & play electrical connection and the IP68 connector included. Clamp bracket included.


110V version upon request

### Main specifications

<b>Mounting</b>	Ceiling and wall surface	<b>Autoprotected Lamp</b>	No
<b>Light source replaceable</b>	Replaceable (LED only) light source by a professional	<b>Number of heads</b>	1
<b>LED type</b>	LED array	<b>Source Power (W)</b>	9.5
<b>Lamp category</b>	LED	<b>Source Flux (lm)</b>	1055
<b>Dimmable</b>	No	<b>System Flux (lm)</b>	613

### Optical

<b>Lighting Type</b>	Direct
<b>Lighting distribution</b>	Symmetric
<b>CCT (K)</b>	2700
<b>CRI&gt;</b>	80
<b>Cold Beam Lighting</b>	No
<b>Beam angle C0-180 (°)</b>	112
<b>Beam angle C90-270 (°)</b>	112



Beam Angle: 112°		
h(m)	E(lx)	D(m)
1	217	2.95
2	54	5.91
3	24	8.86
4	14	11.81
5	9	14.76

Luminous flux luminaire  
613 lm



### Electrical

<b>Insulation class</b>	I	<b>Dimmable type</b>	Non Dimmable
<b>Frequency (Hz)</b>	50-60	<b>Batteries Inside</b>	No
<b>Main Voltage (Vac)</b>	220-240	<b>Power supply replaceable</b>	Replaceable control gear by a professional
<b>Driver</b>	Integrated	<b>Precabled</b>	no
<b>Dimmable</b>	No	<b>Emergency Type</b>	No

### Physical

<b>Colour</b>	Deep Brown	<b>Length (mm)</b>	336
<b>Trim</b>	No	<b>Net weight (kg)</b>	2.1
<b>Orientations</b>	Fixed	<b>IP</b>	65
<b>Recessed depth (mm)</b>	0		
<b>Spot diameter (mm)</b>	208		

### Note

110V version upon request.