









Clessidra 20°+20°

■ F1583018 - Deep Brown

Designed by Antonio Citterio

 $Diffused\ direct/indirect-light\ wall\ lighting\ device.\ Body\ obtained\ by\ means\ of\ aluminium\ pressofusion\ and$ diffusers in PMMA. Aluminium wall attachment with cover in PA66. Available in white-painted or chrome $plated for\ indoor\ version\ and\ dark\ brown-painted\ or\ dark\ gray-painted\ for\ outdoor\ version\ .\ High-efficiency$ lenses specially designed for the application, non-replaceable. Wide range (100-240Volt) power pack integrated in the body. Level IP55

Main specifications

LED type

Optical

CCT (K)

Lighting Type Lighting distribution

Cold Beam Lighting

Extreme Cut off

Mounting	Wall	Lamp holder	COB LED
Environment	Indoor Outdoor	Autoprotected Lamp	No
	wet location	Number of heads	2
Light source type	LED	Source Power (W)	10
Light source replaceable	Replaceable	System Flux (lm)	637

(LED only) light source by a professional

Indirect, Direct


Symmetric

3000

Νo

Νo

LED array



Insulation class Batteries Inside Νo 50/60 Frequency (Hz) Power supply replaceable Replaceable Main Voltage (Vac) 100-240 control gear by Driver Integrated a professional Non Dimmable Dimmable type **Charging Min Time** Νo

Physical

Electrical

Colour	Deep Brown
Net weight (kg)	1.1
Gross weight (kg)	2.43
IP	55
IP external	55