


NOVA U Slide desks



H 743



L 1400; 1600
W 700; 800



L 1400; 1600
W 1440; 1640



L 2800; 3200
W 1440; 1640



L 1400; 1600
W 1440; 1640



Possibility to extend the length of the 2 or 4 desk bench by ordering supplementary units.
We recommend to connect up to 6 back to back units.

FEATURES

- Easy to assemble and disassemble - "metal to metal" construction
- Just one tool for assembling (DIN911 S5)

QUALITY STANDARD

- LST EN 527-1:2011
- LST EN 527-2:2017
- LST EN 1730:2012

TECHNICAL INFORMATION

Desktop

- 25 mm MFC (melamine) with 2 mm ABS edging;
- 10 mm gap between the legs and the desktop;
- 40 mm gap between the desktops in back to back benches (depth of benches – 1440/1640).

Metal beam

- Metal tube - 40x20 mm;
- With welded metal plates for leg fixing;
- Powder coated metal, colour matches the legs.


Legs

- Welded metal tube - 40x40 mm;
- Powder coated metal;
- Plastic feet with height levelling (+10 mm).

GUARANTEE


- 5 years

Sliding desktop for wire management




7mm gap between 4 desk bench sliding desktops

4mm gap between any two sliding desktops standing together



Must be ordered

(for desktop with cut-out)



Metal grommet:
317x119 mm,
H=27 mm

Optional




Power socket blocks



Cable trays



Cable clips



Cable ducts