

UNI cabinets



QUALITY STANDARD

- LST EN 14073-1:2004
- LST EN 14073-2:2004
- LST EN 14073-3:2004
- LST EN 14074-2004

TECHNICAL INFORMATION

Carcass

- 18 mm MFC (melamine) with 1 mm ABS edging.

Top and bottom

- 25 mm MFC (melamine) with 2 mm ABS edging.

Back

- Made of 16 mm MFC (melamine);
- Fabric back panel (X0Z071, X0Z103): HDF 3 mm coated with foam 3 mm and fabric;
- Whiteboard back panel (X0Z070, X0Z102): HPL 1 mm.

Shelves

- 18 mm MFC (melamine) with 1 mm ABS edging, load capacity – 25 kg;
- 25 mm MFC (melamine) with 2 mm ABS edging (for W=1000 mm wide carcass), load capacity – 32 kg;
- Fixed or height adjustable shelves.

Doors

- Doors with hinges in 18 mm MFC (melamine) with 1 mm ABS edging;
- Sliding doors in 18 mm MFC (melamine) with 1 mm ABS edging (with plastic runners);
- Tambour doors from ABS profile;
- 5 mm tempered clear glass.

Handles (2 types)

- 136 mm length square handle, powder coated metal;
- 150 mm length curved handle, powder coated metal.



Handle type (colour + handle code)

Drawers

- File drawers for both A4 and foolscap files;
- Full extension, central locking with anti-tilt function;
- Made of welded metal sheet, without bottom. Powder coated black metal;
- Ball bearing slide, load capacity - 50 kg.

Fittings

- Cams with connecting bolts;
- Lock with metal bars;
- Fast assembling hinges (does not require any tools to connect hinges and plates).

Plinth

- Made of 18 mm MFC (melamine), H=80 mm.

Metal legs

- Metal tube - 40x40 mm;
- Plastic feet with height levelling, H=80 mm +10 mm;
- Powder coated metal.

Plastic legs

- Black plastic height levelling feet, H=23 mm +10 mm.

Castors

- Four twin wheel castors, Ø80 mm;
- Two out of four with stopper brakes;
- The load capacity: 100 kg per castor.

GUARANTEE

- 5 years

